ELONMEK
Tianjin Yining Meike Fine Chemical Co., Ltd.
No.197 Yuguan Road, Hebei District, Tianjin 300400, China

www.elonmek.com
fwj.tjs@gmail.com

224 / 224P High-Fatty-Acid-Ester Emulsion Defoamer

Grades: 224, 224P · Form: Fatty acid ester emulsion · Chemistry group: Mineral Oil & Polyether Ester

1. Product description

High-fatty-acid-ester emulsion defoamer for foaming systems where ordinary silicone defoamers are unsuitable. Fast break, excellent dispersion, good water solubility.

2. Typical properties

Property	224	224P
Appearance	White emulsion	White emulsion
Viscosity (25 °C, mPa·s)	100-2000	100-2000
pH	5.5-7.5	5.5-7.5
Ionic type	Non-ionic	Non-ionic

Values in the table are typical and indicative. They describe the grade as normally supplied and are not a contractual specification; the values confirmed for your order are those stated on the order confirmation.

3. Typical applications

Industrial wastewater · Power plant FGD · Chemical cleaning · Wastewater treatment · Emulsion polymerisation · Other aqueous systems

4. Product characteristics

· Fast foam-breaking speed
· Excellent dispersion
· Good water solubility
· For systems where standard silicone is unsuitable

5. Addition and dilution

Typical addition is 0.05–0.5 % on the weight of the foaming system, established in your own trial at process temperature. Emulsion grades are normally diluted with water before addition and added continuously where the foam forms continuously. Diluted emulsions are used within the working shift; do not store them long term.

6. Packaging and storage

Supplied in the packing agreed for the order — drums, IBC totes or composite cartons for powder grades. Store in the closed original packing, out of direct sunlight, within 5–35 °C, and protect emulsions from freezing. Shelf life is stated on the product label; batches are traceable by lot number.

7. Safety and documentation

A model-specific GHS safety data sheet is issued on request for every model listed above; it is not reproduced here because classification follows the exact grade and the destination regulation. Handling guidance for the family: avoid eye and skin contact, use gloves and goggles, ensure ventilation, and do not discharge concentrates to drains.

8. Contact

Tianjin Yining Meike Fine Chemical Co., Ltd.
No.197 Yuguan Road, Hebei District, Tianjin 300400, China
Email: fwj.tjs@gmail.com · Tel / WhatsApp: +86 185 2653 6999
Website: www.elonmek.com/contact — samples and application review on request.

Issued by the ElonMek technical team, Tianjin. This sheet is provided for product introduction and evaluation; it does not constitute a warranty or a delivery commitment.